

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/088687 A1

- (51) International Patent Classification⁷: **H04Q 7/00** (74) Agents: YIM, Peter, J. et al.; Morrison & Foerster LLP, 425 Market Street, San Francisco, CA 94105-2482 (US).
- (21) International Application Number: PCT/US03/10626 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 3 April 2003 (03.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/370,996 8 April 2002 (08.04.2002) US (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patenti (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): AIR-MAGNET, INC. [US/US]; 894 Ross Drive, Suite 200, Sunnyvale, CA 94089 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): KUAN, Chia-Chee [US/US]; 890 Lockhaven, Los Altos, CA 94024 (US). WU, Miles [US/US]; 231 Clara Court, Fremont, CA 94539 (US). AU, Dean [US/US]; 707 Koa Court, Sunnyvale, CA 94086 (US).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: DETERMINING THE STATE OF A STATION IN A LOCAL AREA



(57) Abstract: In a Wireless Local Area Network (WLAN), transmission exchanged between a station (Station) and an access point (AP) is received using a detector (Detector) located adjacent to the station (Station). The received transmission are analyzed to determine the state of the station (Station), where the state of the station (Station) indicates whether the station (Station) has authenticated and/or associated with the access point (AP) in the wireless Local Area Network.

WO 03/088687 A1

DETERMINING THE STATE OF A STATION IN A LOCAL AREA NETWORK

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of an earlier filed provisional application U.S. Provisional Application Serial No. 60/370,996, entitled DETERMINING THE STATE OF A STATION IN A LOCAL AREA NETWORK, filed on April 8, 2002, the entire content of which is incorporated herein by reference.

BACKGROUND

1. Field of the Invention

[0002] The present invention generally relates to wireless local area networks. More particularly, the present invention relates to determining the state of a station in a wireless local area network.

2. Description of the Related Art

[0003] Computers have traditionally communicated with each other through wired local area networks ("LANs"). However, with the increased demand for mobile computers such as laptops, personal digital assistants, and the like, wireless local area networks ("WLANs") have developed as a way for computers to communicate with each other through transmissions over a wireless medium using radio signals, infrared signals, and the like.

[0004] In order to promote interoperability of WLANs with each other and with wired LANs, the IEEE 802.11 standard was developed as an international standard for WLANs. Generally, the IEEE 802.11 standard was designed to present users with the same interface as an IEEE 802 wired LAN, while allowing data to be transported over a wireless medium.

[0005] In accordance with the IEEE 802.11 standard, a station is authenticated and associated with an access point in the WLAN before obtaining service from the access point. During this authentication and association process, the station proceeds through 3 stages or states (i.e., State 1, State 2, and State 3). In State 1,

the station is unauthenticated and unassociated. In state 2, the station is authenticated but unassociated. In State 3, the station is authenticated and associated. If a station is having difficulty obtaining service from an access point, determining the state of the station can assist in trouble shooting the problem.

SUMMARY

[0006] In one embodiment of the present invention, in a wireless local area network, transmissions exchanged between a station and an access point is received using a detector located adjacent to the station. The received transmissions are analyzed to determine the state of the station, where the state of the station indicates whether the station has authenticated and/or associated with the access point in the wireless local area network.

DESCRIPTION OF THE DRAWING FIGURES

[0007] The present invention can be best understood by reference to the following detailed description taken in conjunction with the accompanying drawing figures, in which like parts may be referred to by like numerals:

[0008] Fig. 1 shows an exemplary Open Systems Interconnection (OSI) seven layer model;

[0009] Fig. 2 shows an exemplary extended service set in a wireless local area network ("WLAN");

[0010] Fig. 3 is an exemplary flow diagram illustrating various states of stations in a WLAN;

[0011] Fig. 4 shows an exemplary embodiment of an access point and a station exchanging transmissions; and

[0012] Fig. 5 shows another exemplary embodiment of an access point and a station exchanging transmissions.

DETAILED DESCRIPTION

[0013] In order to provide a more thorough understanding of the present invention, the following description sets forth numerous specific details, such as

specific configurations, parameters, examples, and the like. It should be recognized, however, that such description is not intended as a limitation on the scope of the present invention, but is intended to provide a better description of the exemplary embodiments.

[0014] With reference to Fig. 1, an exemplary Open Systems Interconnection (OSI) seven layer model is shown, which represents an abstract model of a networking system divided into layers according to their respective functionalities. In particular, the seven layers include a physical layer corresponding to layer 1, a data link layer corresponding to layer 2, a network layer corresponding to layer 3, a transport layer corresponding to layer 4, a session layer corresponding to layer 5, a presentation layer corresponding to layer 6, and an application layer corresponding to layer 7. Each layer in the OSI model only interacts directly with the layer immediately above or below it.

[0015] As depicted in Fig. 1, different computers can communicate directly with each other only at the physical layer. However, different computers can effectively communicate at the same layer using common protocols. For example, one computer can communicate with another computer at the application layer by propagating a frame from the application layer through each layer below it until the frame reaches the physical layer. The frame can then be transmitted to the physical layer of another computer and propagated through each layer above the physical layer until the frame reaches the application layer of that computer.

[0016] The IEEE 802.11 standard for wireless local area networks ("WLANs") operates at the data link layer, which corresponds to layer 2 of the OSI seven layer model, as described above. Because IEEE 802.11 operates at layer 2 of the OSI seven layer model, layers 3 and above can operate according to the same protocols used with IEEE 802 wired LANs. Furthermore, layers 3 and above can be unaware of the network actually transporting data at layers 2 and below. Accordingly, layers 3 and above can operate identically in the IEEE 802 wired LAN and the IEEE 802.11 WLAN. Furthermore, users can be presented with the same interface, regardless of whether a wired LAN or WLAN is used.

[0017] With reference to Fig. 2, an example of an extended service set, which forms a WLAN according to the IEEE 802.11 standard, is depicted having three basic service sets ("BSS"). Each BSS can include an access point ("AP") and one or more stations. A station is a component that can be used to connect to the WLAN, which can be mobile, portable, stationary, and the like, and can be referred to as the network adapter or network interface card. For instance, a station can be a laptop computer, a personal digital assistant, and the like. In addition, a station can support station services such as authentication, deauthentication, privacy, delivery of data, and the like.

[0018] Each station can communicate directly with an AP through an air link, such as by sending a radio or infrared signal between WLAN transmitters and receivers. Each AP can support station services, as described above, and can additionally support distribution services, such as association, disassociation, distribution, integration, and the like. Accordingly, an AP can communicate with one or more stations within its BSS, and with other APs through a medium, typically called a distribution system, which forms the backbone of the WLAN. This distribution system can include both wireless and wired connections.

[0019] With reference to Figs. 2 and 3, under the current IEEE 802.11 standard, each station must be authenticated to and associated with an AP in order to become a part of a BSS and receive service from an AP. Accordingly, with reference to Fig. 3, a station begins in State 1, where the station is unauthenticated to and unassociated with an AP. In State 1, the station can only use a limited number of frame types, such as frame types that can allow the station to locate and authenticate to an AP, and the like.

[0020] If a station successfully authenticates to an AP, then the station can be elevated to State 2, where the station is authenticated to and unassociated with the AP. In State 2, the station can use a limited number of frame types, such as frame types that can allow the station to associate with an AP, and the like.

[0021] If a station then successfully associates or reassociates with an AP, then the station can be elevated to State 3, where the station is authenticated to and associated with the AP. In State 3, the station can use any frame types to

communicate with the AP and other stations in the WLAN. If the station receives a disassociation notification, then the station can be transitioned to State 2.

Furthermore, if the station then receives a deauthentication notification, then the station can be transitioned to State 1. Under the IEEE 802.11 standard, a station can be authenticated to different APs simultaneously, but can only be associated with one AP at any time.

[0022] With reference again to Fig. 2, once a station is authenticated to and associated with an AP, the station can communicate with another station in the WLAN. In particular, a station can send a message having a source address, a basic service set identification address ("BSSID"), and a destination address, to its associated AP. The AP can then distribute the message to the station specified as the destination address in the message. This destination address can specify a station in the same BSS, or in another BSS that is linked to the AP through the distribution system.

[0023] Although Fig. 2 depicts an extended service set having three BSSs, each of which include three stations, an extended service set can include any number of BSSs, which can include any number of stations.

[0024] As described above, according to the current IEEE 802.11 standard, a station is authenticated and associated with an AP to become a part of a BSS and thus obtain service. As also described above, the steps in the authentication and association process is categorized into 3 states (i.e., State 1, State 2, and State 3). Determining the state of a station can be desirable, particularly in analyzing problems that the station may be experiencing in obtaining service.

[0025] For example, with reference to Fig. 4, assume that a station is having difficulty in obtaining service from an AP. Determining if the station is able to reach State 1, State 2, or State 3 can assist in trouble shooting the problem.

[0026] Thus, a detector can be located in the WLAN such that the detector can receive transmissions sent from and received by the station. Note that the detector need not necessarily be physically adjacent the station. Instead, the detector can be sufficiently near or adjacent the station such that the reception range of the detector covers the station.

[0027] By examining the transmissions sent from and received by the station, the detector can determine the state of the station. More particularly, different types of transmissions can be identified as being indicative of different states. For example, in the following table are different types of transmissions and the state that they indicate:

| Type of Transmission | State |
|---|--|
| Probe Request Transmitted by Station | 1 |
| Probe Response Transmitted by AP | 1 |
| Authentication Request Transmitted by Station | 1 |
| Authentication Response w/ Challenge Text Transmitted by AP | 1 |
| Authentication Challenge Response Transmitted by Station | 1 |
| Authentication Final Response Transmitted by AP | 1 - on negative response 2 - on positive response |
| Deauthentication Transmitted by AP | 1 |
| Disassociation Transmitted by AP | 1 |
| Association Request Transmitted by Station | 2 |
| Association Response Transmitted by Station | 2 - on negative response 3 - on positive response |
| Higher Layer Protocol Data Transmitted by Station or AP | 3 |

Table 1

[0028] Thus, when a transmission sent to or from the station is received, the detector examines the transmission to determine if the transmission is one of the types of transmissions listed above. If it is, then the detector can determine the state of the station that received or sent the transmission.

[0029] For example, if the detector receives a probe request frame sent by the station, then the detector can determine that the station is at State 1. If the detector receives a probe response frame sent by the AP to the station, then the detector can determine that the station is at State 1. If the station receives a data

frame, which is a higher layer protocol data, sent by the station or received by the station, then the detector can determine that the station is at State 3.

[0030] The detector can also be configured to display the types of transmissions as a checklist. For example, the following checklist can be displayed:

| |
|--|
| Beacon received by Station |
| Probe request sent by Station |
| Probe response received by Station |
| Auth. request sent by Station |
| Auth. challenge received by Station |
| Auth. challenge response received by Station |
| Auth. final response received by Station |
| Assoc. request sent by Station |
| Assoc. response received by Station |
| Data sent by Station |
| Data received by Station |

Table 2

[0031] When one of the transmissions on the list is detected, then that type of transmission is marked. For example, if an authorization request sent by the station is received, the detector can “check off” the “Auth. request sent” line from above. In this manner, the user of the detector, such as an administrator of the WLAN or a trouble-shooter, can more easily determine the state of the station.

[0032] Additionally, as will be explained below, a station can use one or more channels. As such, a separate checklist can be provided for each of the available channels.

[0033] With reference to Fig. 5, as described above, before a station can receive service from an AP, the station must be authenticated. In order to increase security, an authentication protocol can be implemented in a WLAN environment, such as the extensible authentication protocol over LANs (EAPOL) protocol in accordance with the IEEE 802.1x standard.

[0034] In accordance with the current EAPOL protocol, a station wanting to be authenticated, which is referred to as a supplicant, is authenticated using an authentication server, such as a remote authentication dial in user service (RADIUS) server. As depicted in Fig. 5, the station communicates with the AP,

and the AP, which is referred to as the authenticator, communicates with the authentication server to authenticate the station.

[0035] During the authentication process, the station, AP, and authentication server exchange a number of transmissions. More specifically, in one exemplary mode of operation, the AP sends an "EAP-Request/Identity" transmission to the station. The station then sends an "EAP-Response/Identity" transmission to the AP. The AP then sends the received "EAP-Response/Identity" transmission to the authentication server. In response, the authentication server sends a challenge to the AP, such as with a token password system. The AP sends the challenge to the station as a credential request. The station sends a response to the credential request to the AP. The AP sends the response to the authentication server. If the response from the station is proper, the authentication server sends an "EAP-Success" transmission to the AP, which sends the package to the station. If the response is improper, the authentication server sends an "EAP-Failure" transmission to the AP, which sends the transmission to the station. It should be recognized that the number and types of transmissions exchanged between the station, AP, and authentication server can vary depending on the implemented mode of operation.

[0036] As described above, in one exemplary embodiment, a detector can be located in the WLAN such that the detector can receive transmissions sent from and received by the station. Again, note that the detector need not necessarily be physically adjacent the station. Instead, the detector can be sufficiently near the station such that the reception range of the detector covers the station.

[0037] By examining the transmissions sent from and received by the station, the detector can determine the state of the station. More specifically, the detector can receive the transmissions exchanged between the station and the AP during the authentication process described above in accordance with the EAPOL protocol. The detector can then determine the state of the station based on the received transmissions. More particularly, because the EAPOL transactions occur in state 3 as 802.11 data, the station can be determined as being in state 3.

[0038] Additionally, the detector can also be configured to display the types of transmissions as a checklist. For example, the following checklist can be displayed:

| |
|---|
| 802.1X initiated sent by Station |
| Identity request sent by Station |
| Identity response received by Station |
| Credential request sent by Station |
| Credential response received by Station |
| 802.1X authentication OK by Station |
| 802.1X authentication failed by Station |
| De-authentication sent by Station |
| Data sent by Station |
| Data received by Station |

Table 3

[0039] When one of the transmissions on the list is detected, then that type of transmission is marked. For example, if an "EAP-Request/Identity" package sent by the AP is received, the detector can "check off" the "Identity request sent" line from above. In this manner, the user of the detector, such as an administrator of the WLAN or a trouble-shooter, can more easily determine the state of the station.

[0040] Additionally, as will be explained below, a station can use one or more channels. As such, a separate checklist can be provided for each of the available channels.

[0041] To identify the transmissions sent from and received by the station, the detector obtains the MAC address of the station, which can be obtained from the source and destination address fields of the transmitted frames. The MAC address can also be obtained directly from the station. Alternatively, the MAC address of the station can be stored and retrieved from a table of MAC address assignments, which can be maintained by an administrator of the WLAN.

[0042] Additionally, if a particular AP that the station is attempting to communicate is known, the particular channel that the AP is operating on can then be monitored. If the station is attempting to communicate with multiple APs and the identity of those APs are known, then the particular channels that those APs are operating on can then be monitored.

[0043] Furthermore, the detector can scan the channels of the wireless local area network to receive transmissions sent from and received by the station with known or unknown APs. As described above, in the current implementation of the IEEE 802.11 standard, a total of 11 channels are used in the US, 13 channels are used in Europe, and 14 channels are used in Japan. For the sake of convenience, the following description will assume that the detector and the WLAN are located in the US. However, note that the detector can be configured to operate with any number of channels and in various countries.

[0044] In one configuration, the detector is configured to begin scanning by monitoring channel 1, then scan down each of the remaining 10 channels. If a station is having difficulty obtaining service, it will typically switch channels and repeat the association attempt therefore repeating the association failure scenario. A station can continuously cycle through the channels in an effort to obtain service. As such, the detector is configured to monitor a particular channel for a sufficient amount of time so that the station can complete one or more cycles. For example, the detector can be configured to monitor each channel for about 3 seconds.

[0045] If no transmissions are detected after scanning all of the channels, then the station is rebooted. As described above, a station can be configured to cycle repeatedly through the channels in an attempt to obtain service. However, a station can also be configured to only attempt one cycle and to stop after the last channel has been attempted. When the station is rebooted, it typically begins operating on channel 1. As such, by rebooting the station and monitoring on channel 1, a transmission sent to or received by the station can be detected. However, a station can take some time to reboot, typically a few seconds. As such, the detector is configured to monitor channel 1 for a longer duration than the other channels. For example, in one configuration, the detector is configured to monitor channel 1 for a period of 30 seconds.

[0046] As described above, the detector can scan the available channels in the WLAN. Alternatively, specific channels can be selected to be scanned. Although the detector scans the channels, it passively receives the transmissions, meaning

that it does not broadcast signals on the WLAN. This has the advantage that additional bandwidth on the WLAN is not consumed.

[0047] The detector can be a station in the wireless local area network.

Additionally, the detector can be mobile, portable, stationary, and the like. For instance, the detector can be a laptop computer, a personal digital assistant, and the like. In addition, the detector can be used by a user as a diagnostic tool, by an administrator as an administrative tool, and the like.

[0048] Although the present invention has been described with respect to certain embodiments, examples, and applications, it will be apparent to those skilled in the art that various modifications and changes may be made without departing from the invention.

CLAIMS

We claim:

1. A method of determining the state of a station in a wireless local area network, wherein the state of the station indicates whether the station has authenticated and/or associated with an access point in the wireless local area network, the method comprising:
 - receiving transmissions exchanged between the station and the access point using a detector located adjacent to the station,
 - wherein the transmissions are exchanged over the wireless local area network; and
 - analyzing the received transmissions to determine the state of the station.
2. The method of claim 1, wherein analyzing comprises:
 - examining a received transmission; and
 - determining an indicative state of the station associated with the received transmission.
3. The method of claim 2, wherein a first state of the station is associated with a first set of transmissions, and wherein determining comprises:
 - determining if the received transmission is one of the first set of transmissions; and
 - identifying the state of the station as being the first state when the received transmission is determined to be one of the first set of transmissions.
4. The method of claim 3, wherein a second state of the station is associated with a second set of transmissions, and wherein determining comprises:
 - determining if the received transmission is one of the second set of transmissions; and
 - identifying the state of the station as being the second state when the received transmission is determined to be one of the second set of transmissions.

5. The method of claim 4, wherein a third state of the station is associated with a third set of transmissions, and wherein determining comprises:
 - determining if the received transmission is one of the third set of transmissions; and
 - identifying the state of the station as being the third state when the received transmission is determined to be one of the third set of transmissions.
6. The method of claim 5, wherein the first state indicates the station has not been authenticated or associated with the access point, the second state indicates that the station has authenticated but not associated with the access point, and the third state indicates that the station has authenticated and associated with the access point.
7. The method of claim 1, wherein the transmissions exchanged between the station and the access point comply with an extensible authentication protocol over local area networks (EAPOL) protocol.
8. The method of claim 1, wherein receiving comprises:
 - obtaining a medium access control (MAC) address of the station;
 - receiving a transmission using the detector, wherein the transmission includes a source address and a destination address; and
 - determining if the source address or the destination address of the transmission is the MAC address of the station.
9. The method of claim 1, wherein receiving comprising:
 - scanning a plurality of channels used in the wireless local area network using the detector; and
 - rebooting the station if no transmissions are received during a scan of the plurality of channels.

10. The method of claim 9, wherein the station operates on a first channel after being rebooted, wherein the first channel is one of the plurality of channels used in the wireless local area network, and further comprising:

scanning on the first channel using the detector for a longer period of time than other channels of the plurality of channels used in the wireless local area network.

11. The method of claim 1, wherein analyzing comprises:

displaying a list of transmissions on the detector, wherein the list includes different types of transmissions potentially exchanged between the station and the access point; and

when a received message corresponds to one of the types of transmissions in the list of transmissions, indicating on the list of transmissions that the type of transmission corresponding to the received message was received.

12. The method of claim 11, wherein the types of transmissions include transmissions exchanged between the station and the access point during an authentication process in accordance with an extensible authentication protocol over local area networks (EAPOL) protocol.

13. A method of determining the state of a station in a wireless local area network, the method comprising:

receiving a transmission exchanged between the station and the access point using a detector located adjacent to the station,

wherein the transmissions are exchanged over the wireless local area network;

displaying a list of transmissions on the detector,

wherein the list includes different types of transmissions potentially exchanged between the station and the access point, and

wherein the different types of transmissions are indicative of different states of the station;

determining if the received transmission is one of the different types of transmissions; and

when a received transmission corresponds to one of the different types of transmissions, indicating on the list of transmissions that the type of transmissions that the type of transmission corresponding to the received transmission was received.

14. The method of claim 13, wherein the types of transmissions include transmissions exchanged between the station and the access point during an authentication process in accordance with an extensible authentication protocol over local area networks (EAPOL) protocol.

15. The method of claim 13, wherein a first type of transmissions is associated with a first state of the station, wherein the first state indicates the station has not been authenticated or associated with the access point.

16. The method of claim 15, wherein a second type of transmissions is associated with a second state of the station, wherein the second state indicates the station has authenticated but not associated with the access point.

17. The method of claim 16, wherein a third type of transmissions is associated with a third state of the station, wherein the third state indicates the station has authenticated and associated with the access point.

18. The method of claim 13, wherein receiving comprising:
scanning a plurality of channels used in the wireless local area network using the detector; and
rebooting the station if no transmissions are received during a scan of the plurality of channels.

19. The method of claim 18, wherein the station operates on a first channel after being rebooted, wherein the first channel is one of the plurality of channels used in the wireless local area network, and further comprising:
 scanning on the first channel using the detector for a longer period of time than other channels of the plurality of channels used in the wireless local area network.
20. The method of claim 13 further comprising:
 examining a received transmission; and
 determining a state of the station associated with the received transmissions.
21. The method of claim 20, wherein a first state of the station is associated with a first set of transmissions, a second state of the station is associated with a second set of transmission, and a third state of the station is associated with a third set of transmissions, and wherein determining comprises:
 determining if the received transmissions is one of the first, second, or third set of transmissions; and
 identifying the state of the station as being the first, second, or third set when the received transmission is determined to be one of the first, second, or third set of transmissions, respectively.
22. An apparatus for determining the state of a station in a wireless local area network, wherein the state of the station indicates whether the station has authenticated and/or associated with an access point in the wireless local area network, the apparatus comprising:
 a detector configured to:
 receive transmissions exchanged between the station and the access point when the detector is located adjacent to the station; and
 analyze the received transmissions to determine the state of the station.

23. The apparatus of claim 22, wherein a first state of the station is associated with a first set of transmissions, at least a second state of the station is associated with at least a second set of transmissions, and wherein the detector is configured to analyze the received transmissions by:

determining if the received transmission is one of the first set or at least the second set of transmissions; and

identifying the state of the station as being the first state or the at least second state when the received transmission is determined to be one of the first set or the at least second set of transmissions.

24. The apparatus of claim 23, wherein the first state indicates the station has not been authenticated or associated with the access point, and wherein the at least second state indicates that the station has authenticated but not associated with the access point

25. The apparatus of claim 24, wherein a third state of the station is associated with a third set of transmissions, wherein the third state indicates that the station has authenticated and associated with the access point, and wherein the detector is configured to analyze the received transmissions by:

determining if the received transmission is one of the third set of transmissions; and

identifying the state of the station as being the third state when the received transmission is determined to be one of the third set of transmissions.

26. The apparatus of claim 22, wherein the transmissions exchanged between the station and the access point comply with an extensible authentication protocol over local area networks (EAPOL) protocol.

27. The apparatus of claim 22, wherein the detector is configured to receive transmissions by:

scanning a plurality of channels used in the wireless local area network, wherein the station is rebooted if no transmissions are received during a scan of the plurality of channels.

28. The apparatus of claim 27, wherein the station operates on a first channel after being rebooted, wherein the first channel is one of the plurality of channels used in the wireless local area network, and wherein the detector is configured to:
scan the first channel for a longer period of time than other channels of the plurality of channels used in the wireless local area network.

29. The apparatus of claim 22, wherein the detector is configured to:
display a list of transmissions, wherein the list includes different types of transmissions potentially exchanged between the station and the access point; and
when a received message corresponds to one of the types of transmissions in the list of transmissions, indicate on the list of transmissions that the type of transmission corresponding to the received message was received.

30. The apparatus of claim 29, wherein the types of transmissions include transmissions exchanged between the station and the access point during an authentication process in accordance with an extensible authentication protocol over local area networks (EAPOL) protocol.

31. A computer-readable storage medium containing computer executable code to determine the state of a station in a wireless local area network, wherein the state of the station indicates whether the station has authenticated and/or associated with an access point in the wireless local area network, by instructing a computer to operate as follows:

receiving transmissions exchanged between the station and the access point; and
analyzing the received transmissions to determine the state of the station.

32. The computer-readable storage medium of claim 31, wherein a first state of the station is associated with a first set of transmissions, at least a second state of the station is associated with at least a second set of transmissions, and wherein analyzing comprises:

determining if the received transmission is one of the first set or at least the second set of transmissions; and

identifying the state of the station as being the first state or the at least second state when the received transmission is determined to be one of the first set or the at least second set of transmissions.

33. The computer-readable storage medium of claim 32, wherein the first state indicates the station has not been authenticated or associated with the access point, and wherein the at least second state indicates that the station has authenticated but not associated with the access point

34. The computer-readable storage medium of claim 33, wherein a third state of the station is associated with a third set of transmissions, wherein the third state indicates that the station has authenticated and associated with the access point, and wherein analyzing further comprises:

determining if the received transmission is one of the third set of transmissions; and

identifying the state of the station as being the third state when the received transmission is determined to be one of the third set of transmissions.

35. The computer-readable storage medium of claim 31, wherein the transmissions exchanged between the station and the access point comply with an extensible authentication protocol over local area networks (EAPOL) protocol.

36. The computer-readable storage medium of claim 31, wherein receiving comprises:

scanning a plurality of channels used in the wireless local area network, wherein the station is rebooted if no transmissions are received during a scan of the plurality of channels.

37. The computer-readable storage medium of claim 36, wherein the station operates on a first channel after being rebooted, wherein the first channel is one of the plurality of channels used in the wireless local area network, and wherein scanning comprises:

scanning the first channel for a longer period of time than other channels of the plurality of channels used in the wireless local area network.

38. The computer-readable storage medium of claim 31, wherein analyzing comprises:

displaying a list of transmissions, wherein the list includes different types of transmissions potentially exchanged between the station and the access point; and

when a received message corresponds to one of the types of transmissions in the list of transmissions, indicating on the list of transmissions that the type of transmission corresponding to the received message was received.

39. The computer-readable storage medium of claim 38, wherein the types of transmissions include transmissions exchanged between the station and the access point during an authentication process in accordance with an extensible authentication protocol over local area networks (EAPOL) protocol.




Fig. 1

2/4




Fig. 2




Fig. 3




Fig. 5




Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/10626

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H04Q 7/00
US CL : 370/338

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 370/338, 241, 252, 277, 278, 282, 328, 349; 379/9.03, 100.05, 100.06; 455/425

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
BRS(EAST), IEEE(Xplore)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| A, P | US 2003/0050068 A1 (WOXBERG et al) 13 March 2003 (13.03.2003), entire document | 1-39 |
| A, P | US 2003/0059039 A1 (MEYERSON et al) 27 March 2003 (27.03.2003), entire document | 1-39 |
| A, p | US 6,345,043 B1 (HSU) 05 February 2002 (05.02.2002), entire document | 1-39 |
| A, P | US 2002/0049567 A1 (VATAJA) 25 April 2002 (25.04.2002), entire document | 1-39 |
| A, P | US 2002/0136184 A1 (LIANG et al) 26 September 2002 (26.09.2002), entire document | 1-39 |
| A | Sheu et al, Dynamic Access Point Approach (DAPA) for IEEE 802.11 Wireless LANs, IEEE 1999, Vol 5, pages 2646-2650. | 1-39 |

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

30 May 2003 (30.05.2003)

Date of mailing of the international search report

10 JUN 2003

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

Ahmed Elallam

Telephone No. (703) 305-4700